

## AMENDMENTS TO THE CLAIMS

### **Claims pending**

- At time of the Action: Claims 1, 2, 12 – 21 and 24 - 26
- After this Response: Claims 1, 2, 12 – 17, 20, 21 and 24, 26

### **Canceled or Withdrawn claims:**

- **Previously:** Claims 3 – 10, 22, and 23
- **Currently:** Claims 11, 16, 18, 19, and 25

**Amended claims:** Claims 1, 12, 13, 17, 20, 24, and 26

### **Listing of Claims**

This listing of the claims will replace all prior versions and listings of claim in the present application.

1. (**Currently Amended**) A data switch comprising:

a plurality of ingress/egress ports for transmitting data packets including a MAC destination address and a MAC origin address, the plurality of ingress/egress ports including a first ingress/egress port and a plurality of other ingress/egress ports; and

address table construction means for generating a table containing associations between the ingress/egress ports of the switch and MAC addresses of any devices connected to the switch via those ingress/egress ports,

wherein the address table construction means is switchable between a first operating state and a second operating state, the address table construction means being operable to:

insert said associations into said table for each of the first and the plurality of other ingress/egress ports when in the first operating state[1], and

stop generation of the table with respect to the first ingress/egress port before MAC addresses of at least some devices operably coupled through the first ingress/egress port are associated with the first ingress/egress port in the table when in the second operating state;

a switching fabric; and

a control unit operable to control the switching fabric, the control unit being arranged, upon receiving a data packet from any of the other ingress/egress ports having a destination address which is not stored in the table, to control the switching fabric to transmit the data packet to the first ingress/egress port.

2. **(Previously Presented)** A data switch according to claim 1 in which the address table construction means is switched between the first and the second operating state according to a setting of a control register.

3. – 11. **(Canceled)**

12. **(Currently Amended)** The device according to claim 441, wherein the first ingress/egress port is adapted to be connected to a communication network.

13. **(Currently Amended)** The device according to claim 441, wherein at least one of the other ingress/egress ports is arranged to receive and transmit voice signals.

14. **(Previously Presented)** The device according to claim 13, further comprising a microphone, a speaker, circuitry configured to transform sound signals received from the microphone into data packets and to transform data packets into control signals for the speaker, and wherein the circuitry is coupled to the at least one of the other ingress/egress ports arranged to receive and transmit voice signals.

15. **(Previously Presented)** The device according to claim 14, further including sockets adapted to connect one or more of the other ingress/egress ports to devices which each have a MAC address.

16. **(Canceled)**

17. **(Currently Amended)** A method of operating a data switch comprising a first ingress/egress port and a plurality of other ingress/egress ports, the method including:

generating a table containing associations between the first and the plurality of other ingress/egress ports of the switch and MAC addresses of any devices connected to the switch thereby when the data switch is in a first operating state;

switching the data switch to a second operating state;

stopping generation of the table with respect to the first ingress/egress port before MAC addresses of at least some devices operably coupled through the first ingress/egress port are associated with the first ingress/egress port in the table

wherein stopping generation of the table occurs after at least one MAC address of at least one device operably coupled through the first ingress/egress port is associated with the first ingress/egress port in the table; and

discarding a data packet received from the first ingress/egress port that does not have a destination address associated according to the table with any of the other ingress/egress ports;

receiving a data packet having a destination port MAC address absent from the generated table; and

forwarding the data packet to the first ingress/egress port.

18. **(Canceled)**

19. **(Canceled)**

20. **(Currently Amended)** The method of claim ~~49~~17, wherein forwarding the data packet further comprising forwarding the data packet only if the data packet was received from one of the plurality of other ingress/egress ports.

21. **(Previously Presented)** The method of claim 17, further comprising:  
converting analog audio signals to data packets; and  
providing the data packets to one of the other ingress/egress ports.

22. – 23. **(Canceled)**

24. **(Currently Amended)** A method of operating a data switch for switching data packets including a destination address, the data switch comprising a plurality of ingress/egress ports, the method comprising:

generating a table containing associations between ports of the switch and MAC addresses of any devices connected to the switch via those ports,

inserting associations into the table for each of the ingress/egress ports of the switch in a first operating state; ~~and~~

stopping generation of the table with respect to a first ingress/egress port before MAC addresses of at least some devices operably coupled through the first ingress/egress port are associated with the first ingress/egress port in the table in a second operating state,

wherein the plurality of ingress/egress ports includes a plurality of other ingress/egress ports, and

wherein the data switch further comprises a memory storing a table containing associations between the other ingress/egress ports and MAC addresses of any devices connected to the switch via the other ingress/egress ports;

receiving a data packet from any of the other ingress output ports; and

transmitting the data packet to the first ingress/egress port if the data packet contains a destination address that is absent from the table.

25. **(Canceled)**

26. **(Currently Amended)** The method of claim ~~25~~24, further comprising:

transmitting the data packet to a corresponding ingress/output port if the data packet contains a destination address that is present on the table.